

BUILT RIGHT - PRICED RIGHT

EASTEY

Shrink Packaging Equipment for the Shrinking World

EH2210E HIGH SPEED SHRINK TUNNEL



- Dual heater banks with dual blowers and controls.
- Conveyor speed - 120 feet per minute
- Package speed - 100 feet per minute, note actual package speed is relative to overall package size and shrink film type and the gauge being used.
- Direction of travel, right to left or left to right.
- Electrical panel mounted on left or right side.
- Cooling fans used to reduce heat retention of the conveyor.
- Base has leveling adjustments and locking casters.
- Positive shrinking with 4 directional air flow.
- Solid state temperature controllers.
- Solid state relays.
- Variable speed electronically controlled air velocity.



Made in the USA

OPTIONS:

- Converts into **high speed bundling tunnel**, by changing the tunnel height to 16" (60 amps) or 20" (70 amps).
- Battery backup. Runs 2 to 3 cycles to clear the chamber.
- Electrical change - 220V (3ph) to 220V (1ph)
- Electrical change - 460/480V (3ph)
- Window



WEIGHT, POWER REQUIREMENTS, DIMENSIONS

Eastey Tunnel Model	Machine Dimensions (in)					Machine Dimensions (cm)					Standard Power			Weight		Crated Shp Wgt	
	W	x	H	x	L	W	x	H	x	L	Volts	Amps	Phase	(lbs)	(kg)	(lbs)	(kg)
EH2210E	41	x	67	x	86	104	x	170	x	219	220	50	3 ph	1200	546	1650	751

TUNNEL CHAMBER, ROLLER AND CONVEYOR DIMENSIONS

Model	Chamber Dimensions (in)				Chamber Dimensions (cm)				Roller Width		Conveyor Length			
	W	x	H	x	L	W	x	H	x	L	(in)	(cm)	(in)	(cm)
EH2210E	20	x	10	x	70	51	x	25	x	178	20	51	86	219

DEALER IMPRINT

EASTEY ENTERPRISES, INC.
 21480 147TH AVE. NO. ROGERS, MN 55374
 PHONE: 763/428-4846 FAX: 763/428-8361
 TOLL FREE 800/835-9344
www.eastey.com
eastey@eastey.com

Copyright © 2005 Eastey Enterprises, Inc., All Rights Reserved