



CHOOSE YOUR CONTROL PANEL BROCHURE ADDITION

M. J. MAILLIS

WULFTEC®

Basic Panel (included in the machine price)



Features:

- Allen Bradley MicroLogix 1000 PLC
- Turntable rotation speed adjustment 0-16 RPM
- Carriage up / down speed adjustment
- Film tension adjustment
- Reinforced wrap
- Manual turntable rotation
- Manual mode carriage up / down
- Top & bottom wrap selector 1-3
- Autoheight sensing photoeye on / off
- Start / Stop push button
- Power On light
- Emergency stop push / pull

Standard Panel - Allows for some options and minor program changes



Features:

- Allen Bradley MicroLogix 1200 PLC
- Separate top and bottom wrap selectors 0-9
- Film tension adjustment
- Separate up / down carriage speeds
- Spiral up, spiral up / down
- Manual mode carriage up / down
- Top cover on / off switch (slash-proof program)
- Reinforced wrap
- Turntable rotation speed adjustment
- Manual turntable rotation
- Autoheight sensing photoeye on / off
- Start / Stop push button
- Power On / Off switch and status light
- Emergency stop push / pull

Deluxe Panel - Allows for a full range of options and program changes

Features:

- Allen Bradley MicroLogix 1200 PLC
- PanelView Plus 600 touch screen
- All standard panel features described above
- Load per hour counter
- Non-resettable cycle counter
- Can store up to 6 different wrap patterns
- Maintenance screen
- Alarm screen, troubleshooting guide and much more...



WE FEAR NO PACKAGING CHALLENGE
www.wulftec.com



CHOOSE YOUR OPTIONS BROCHURE ADDITION

WULFTEC®

HEIGHT EXTENSION OPTIONS

1. Increase wrap height to 92"
2. Increase wrap height to 104"
3. Increase wrap height to 116"
4. Increase wrap height to 128" (*available for Low-profile stretch wrappers only*)

CONTROL PANEL OPTIONS

1. Upgrade to **STANDARD** control panel
(see next page for complete description)
2. Upgrade to **DELUXE** control panel
(see next page for complete description)

CARRIAGE OPTIONS

1. Upgrade to 30" NO-THREAD powered pre-stretch carriage
2. 20" hydraulic carriage (No pre-stretch) to replace standard carriage (inc. tension bypass)
3. 30" hydraulic carriage (No pre-stretch) to replace standard carriage (inc. tension bypass)

OTHER OPTIONS

1. Smart Loading Ramp (*available for Low-profile stretch wrappers only*)
2. Background Suppression Photoeye for dark or shiny loads autoheight detection.
3. Power Transformer – required for unit to be a voltage other than 120V/1/60
4. Pull cord to start and stop cycle.



CHOOSE YOUR COMBINATIONS BROCHURE ADDITION

LOW PROFILE TURNTABLE


Octagonal base

SML-150-B (Basic control panel)
SML-150-S (Standard control panel)
SML-150-D (Deluxe control panel)
80" wrap height
20" NO-THREAD powered pre-stretch carriage
58" diameter, 4,000 lb. capacity
Max load size 50"W x 50"L (70.7" dia.)




Standard base

SML-200-B (Basic control panel)
SML-200-S (Standard control panel)
SML-200-D (Deluxe control panel)
80" wrap height
20" NO-THREAD powered pre-stretch carriage
65" diameter, 5,000 lb. capacity
Max load size 55"W x 55"L (78" dia.)




Standard 2' extension base

SML-EXT-B (Basic control panel)
SML-EXT-S (Standard control panel)
SML-EXT-D (Deluxe control panel)
80" wrap height
20" NO-THREAD powered pre-stretch carriage
65" diameter, 5,000 lb. capacity
Max load size 55"W x 55"L (78" dia.)



Oversized base


SML-277-B (Basic control panel)
SML-277-S (Standard control panel)
SML-277-D (Deluxe control panel)
80" wrap height
20" NO-THREAD powered pre-stretch carriage
77" diameter, 5,000 lb. capacity
Max load size 65"W x 65"L (92" dia.)



HIGH PROFILE TURNTABLE


Octagonal base

SMH-150-B (Basic control panel)
SMH-150-S (Standard control panel)
SMH-150-D (Deluxe control panel)
80" wrap height
20" NO-THREAD powered pre-stretch carriage
51" width, 4,000 lb. capacity
Max load size 58"W x 58"L (82" dia.)



Standard base

SMH-200-B (Basic control panel)
SMH-200-S (Standard control panel)
SMH-200-D (Deluxe control panel)
80" wrap height
20" NO-THREAD powered pre-stretch carriage
51" width, 5,000 lb. capacity
Max load size 58"W x 58"L (82" dia.)



Split base

SMH-SPL-B (Basic control panel)
SMH-SPL-S (Standard control panel)
SMH-SPL-D (Deluxe control panel)
80" wrap height
20" NO-THREAD powered pre-stretch carriage
extends up to 3 feet
51" width, 5,000 lb. capacity
Max load size 58"W x 58"L (82" dia.)



Extra heavy-duty base

SMH-HVY-B (Basic control panel)
SMH-HVY-S (Standard control panel)
SMH-HVY-D (Deluxe control panel)
80" wrap height
20" NO-THREAD powered pre-stretch carriage
51" width, 8,000 lb. capacity
ring-gear driven (10-year warranty)
Max load size 58"W x 58"L (82" dia.)

